

NAME

`git-qheader` – display log message text from a patch header

SYNOPSIS

`git qheader` [*<patch>*]

DESCRIPTION

The **git qheader** command displays the commit log message text, as recorded in the header of any **Git-MQ** patch which is specified by the *<patch>* argument; if no *<patch>* argument is specified, the displayed log message is retrieved from the topmost currently-applied patch, if any.

EXIT STATUS

On successful completion, **git qheader** reports an exit status code of 0. Any non-zero exit status code indicates that an error occurred.

COMPARISON WITH MERCURIAL QUEUES

Inspired by, and for the most part based on behavioural observation of **Mercurial**'s **MQ** extension, the **git qheader** command exhibits fundamentally the same behaviour as its **hg qheader** counterpart.

AUTHOR

Copyright (C) 2019, by Keith Marshall

This man page was written by Keith Marshall <keith@users.osdn.me>, to accompany the **Git-MQ** program suite. It is published under the terms of the GNU Free Documentation Licence, version 1.3, (or any later version published by the Free Software Foundation), with no Invariant Sections, no Front-Cover Texts, and no Back-Cover Texts.

The **Git-MQ** program suite itself is distributed under the terms of the GNU General Public Licence, version 3, (or any later version published by the Free Software Foundation).

Copies of the GNU Free Documentation Licence, and of the GNU General Public Licence, are included within the **Git-MQ** source distribution, in the files **FDL-1.3**, and **LICENCE**, respectively.

SEE ALSO

`git-qseries`(1)